

◆ Characteristic / 特點：

- Special line-out design for bending resistance and tensile.it will upgrade the durability and life.
/ 獨特的出線包覆設計，抗拉、耐彎曲，提升耐用度和壽命。
- The IP67 rating is designed to the effective waterproof.
/ 保護結構達到IP67的規格，能有效的防水。
- NP model：NPN+PNP NO/NC 4-in-1 outputs.
/ 新型NP電路：NPN/PNP NO/NC All in one.



◆ Specifications / 規格表：

Output method /輸出模式	NPN N.O.	PSC1806-N	PSC1806-NK	PSC1812-N	PSC1812-NK
	PNP N.O.	PSC1806-P	PSC1806-PK	PSC1812-P	PSC1812-PK
	NPN N.O./N.C. PNP N.O./N.C.	PSC1805-NP	PSC1805-NPK	PSC1808-NP	PSC1808-NPK
	2 WIRES N.O.	—	—	—	—
	2 WIRES N.C.	—	—	—	—
Sensing distance / 檢出距離		6 mm / 5 mm		12 mm / 8 mm	
Secure sensing distance / 建議距離		0 to 4.8 mm / 0 to 4.0 mm		0 to 9.6 mm / 0 to 6.4 mm	
Standard sensing object / 標準檢測物		Iron 18× 18 × 1 mm			
Sensing type / 檢出方式		Shielded / 隔離型		Unshielded / 非隔離	
Description / 外型		Standard M18 / 標準M18			
Hysteresis / 遲滯		≤ 10 % of sensing distance			
Response time / 反應時間		2 ms Max.			
Operating voltage / 工作電壓		DC 12 ~ 24 V			
Current consumption / 消耗電流		≤ 14 mA no-load			
Load current / 負載電流		100 mA Max. at DC 24V			
Leakage current / 漏電流		≤ 1.1 mA no-load			
Residual voltage / 殘餘電壓		≤ DC 2V			
Insulation resistance / 隔離阻抗		20MΩ min. (DC500V)			
Voltage withstandability / 絕緣耐壓		AC1000V 60Hz for 60 Sec.			
Operating temperature / 工作溫度		-20℃ ~ + 60℃			
Protection degree / 防水等級		IP 67			
Wiring method / 出線方式		N/P:Ø5.2x2M/3-wires NP:Ø5.2x2M/4-wires	M12 pigtailed type / M12接頭15cm電線式	N/P:Ø5.2x2M/3-wires NP:Ø5.2x2M/4-wires	M12 pigtailed type / M12接頭15cm電線式
Weight / 重量		Approx.93g	Approx.40.5g	Approx.92g	Ap prox.39.5g

◆ Dimensions / 尺寸圖： (unit:mm)

◆ Wiring diagrams / 接線圖：

